R-625 HYDRAULIC DRILLING RIG



YEAR OF MANUFACTURE SERIAL NUMBER CONFIGURATION

PRICE

2006 2441 CFA –

COMPACT PILE £POA

Ex Works, UK

The R-625 drilling rig is a versatile rig designed to suit various drilling applications including use with a Kelly bar and the Continuous Flight Auger drilling technique.

Features include:

Completely self erecting
High reliability and safety
Extendable tracks from 3m to 4.5m
70 ton class machine
High production
360° turret rotation

SPECIFICATION:

In CFA Compact Pile Configuration

Max. Drilling Diameter: 1200mm

Max. Drilling Depth: 20.5m in compact

configuration

Max. Extraction Force: 732 kN


Max. Torque: 240 kNm

Max. Drilling Speed: 30 rpm

Operating Weight: 70 ton

Full service and operational check

completed.



Diesel engine		
Make/Model		Deutz TCD 2015V06 Tier III
Max Power	kW (HP)	300 (402)@ 2000rpm
Hydraulic pumps		
Main Pumps	lt/min	2 x 280
Main Winch		
1 st layer Nominal line pull	kN	240
Auxiliary winch		
1 st layer Nominal line pull	kN	140
Rotary Table		
Nominal Torque	kNm	240
Maximum drilling speed	rpm	30
Max Extraction force	kN	732



Robin North – Managing Director

Phone: 0044 (0)1832 274602 Fax: 0044 (0)1832 274677 Mobile: 0044 (0)7721 514005 E-mail: robin@soilmec.co.uk