CM-120 HYDRAULIC DRILLING RIG



YEAR OF MANUFACTURE SERIAL NUMBER CONFIGURATION PRICE 1999 1532 CFA £POA Ex Works, UK

The CM-120 drilling rig is dedicated to the Continuous Flight Auger drilling technique.

Features include:

Completely self erecting
High reliability and safety
Extendable tracks from 2.5 to 3.9m
High production
360° turret rotation

SPECIFICATION:

In CFA Configuration

Max. Drilling Diameter: 1400mm

Max. Drilling Depth: 24.5m + 6m with

kelly extension

Max. Torque: 250 kNm

Operating Weight: 105 ton

Full service and operational check completed.



Diesel engine		
Make/Model		DEUTZ BF8M1015C
Max Power	kW (HP)	400 (544)@ 2100rpm
Hydraulic pumps		
Main Pumps	lt/min	2 x 380
Max working pressure	MPa	35
Main Winch		Type SW-290
1 st layer Nominal line pull	kN	290
1 st layer nominal rope speed	m/min	50/80
Rope Diameter	Mm	30
Auxiliary winch		Type SW -140
1 st layer Nominal line pull	kN	140
1 st layer nominal rope speed	m/min	60/120
Rope Diameter	Mm	26
Rotary Table		
Nominal Torque	kNm	<u>300@9.5</u> rpm
Maximum drilling speed	rpm	25



Mark Nelson - General Manager

Phone: 0044 (0)1832 274602 Fax: 0044 (0)1832 274677 Mobile: 0044 (0)7768 890564 E-mail: mark@soilmec.co.uk