CM-70 HYDRAULIC DRILLING RIG



YEAR OF MANUFACTURE SERIAL NUMBER CONFIGURATION PRICE 2005 2286 CFA £POA Ex Works, UK

The CM-70 drilling rig is dedicated to the Continuous Flight Auger drilling technique.

Features include:

Completely self erecting
High reliability and safety
Quick installation
Extendable tracks from 2.5 to 3.9m
Easy manoeuvrability
Low transport costs
High production
360° turret rotation

SPECIFICATION:

In CFA Configuration

Max. Drilling Diameter: 1000mm

Max. Drilling Depth: 22m + 6m with

kelly extension

Max. Extraction Force: 680 kN

Max. Torque: 153 kNm

Max. Drilling Speed: 26 rpm

Operating Weight: 60 ton

Full service and operational check

completed.



| Diesel engine | | |
|--|---------|----------------------------|
| Make/Model | | CATERPILLAR 31268 Attach 1 |
| Max Power | kW (HP) | 231 (310)@ 2500rpm |
| Hydraulic pumps | | |
| Main Pumps | lt/min | 2 x 230 |
| Max working pressure | MPa | 32.5 |
| Main Winch | | Type SW-170 |
| 1 st layer Nominal line pull | kN | 170 |
| 1 st layer nominal rope speed | m/min | 73 |
| Rope Diameter | Mm | 24 |
| Auxiliary winch | | Type SW - 90.3 |
| 1 st layer Nominal line pull | kN | 75 |
| 1 st layer nominal rope speed | m/min | 58 |
| Rope Diameter | Mm | 19 |
| Rotary Table | | |
| Nominal Torque | kNm | 153@8.0rpm |
| Maximum drilling speed | rpm | 26 |



Mark Nelson - General Manager

Phone: 0044 (0)1832 274602 Fax: 0044 (0)1832 274677 Mobile: 0044 (0)7768 890564 E-mail: mark@soilmec.co.uk